

# 智能模块 Smart LCD

## Highlights

TOPWAY's Smart LCDs embed a display engine and a versatile range of TFT display sizes and Touch-Panels to support a wide range of industrial and instrumentation applications.


The pre-loaded User Interface (UI) reduces the host system's workload and provides a much faster interaction with the user.

UI designs are implemented under usage of TOPWAY's Graphics Editor allowing designs with zero coding. It dramatically simplifies and speeds up the whole product design process.

TOPWAY 智能模块专为工业显示应用而设计。将 PC 上的各种显示图案可以预存在模块内，并能实现快速的画面变换和刷新，从而让客户的产品可以轻松拥有精彩的显示界面。

不仅如此，应用智能模块可以极大地减轻了主机对显示界面的负荷，降低了对主机的要求，从而可降低系统设计成本，而且更加稳定可靠。

## Smart LCD vs. Conventional TFT



## Main Specification

Display : 5.0", 7.0", 8.0" Industrial TFT Display  
 Backlight : High Brightness LEDs Backlight  
 Touch Panel : Industrial Resistive/Capacitive Touch Panel  
 Memory : 256M Byte high speed flash (equivalent to 349 background images)  
 Operating Temperature : -20 ~ +70°C  
 Storage Temperature : -30 ~ +80°C

## Major Models

Model	Outline (mm)	Resolution	I/F	T/P	Note
HMT050CC-C	143.5 x 80.9 x 14.8	800 x 480	RS-232C	O	
HMT070CE-C	185.9 x 109.5 x 19.4	800 x 480	RS-232C	O	
HMT080EB-C	196.0 x 143.9 x 17.2	800 x 600	RS-232C	O	

For semi-custom made or full-custom made products, please contact us for further information & options.  
 可按客户要求提供半定制与全定制产品，其他产品与更详细资料请与我们联系。

## Pages, Elements, Picture Resources, Variables and Functions

